



# Xiangtan Huaxing Material Co., Ltd.



## SKF SAKAC 10 M Spherical Plain Bearings - Rod Ends

Bearing No. SAKAC 10 M

SAKAC 10 M Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.05
EAN	7316577027641
Product Group	B04286
Stud Profile	Male
Mounting Thread	M10 X 1.5
Thread Direction	Right Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Bronze
Relubricatable	Yes
Enclosure	Open
Other Features	3 Piece   Zinc Plated Outer
Long Description	10MM Bore; 10.5MM House Width; Male Stud Profile; M10 X 1.5; Right Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Bro
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod Ends



## Xiangtan Huaxing Material Co., Ltd.

UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SAKAC 10 M
Weight / LBS	0.119
d	0.394 Inch   10 Millimeter
Housing Width	0.413 Inch   10.5 Millimeter
Ball Width	0.551 Inch   14 Millimeter
bore diameter:	10 mm
ball material:	Steel
misalignment angle:	13 °
race material:	Bronze
shank thread length:	28 mm
radial static load capacity:	10.8 kN
rod end type:	Male Threaded
operating temperature range:	-30 to +180 ° F
shank thread size:	M10x1.5
head diameter:	29 mm
thread direction:	Right Hand
head width:	10.5 mm
grade:	Precision
ball width:	14 mm
lubrication type:	With Lubrication Fitting
length to ball center:	48 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, DIN 3405:1986
d	10 mm
d <sub>2</sub> max.	29 mm



## Xiangtan Huaxing Material Co., Ltd.

B	14 mm
G	M 10
C <sub>1</sub> max.	11.5 mm
h	48 mm
	13 °
d <sub>k</sub>	19 mm
l <sub>1</sub> min.	28 mm
l <sub>2</sub> max.	64 mm
r <sub>1</sub> min.	0.3 mm
Basic static load rating C <sub>0</sub>	10.8 kN
Specific dynamic load factor K	50 N/mm <sup>2</sup>
Material constant K <sub>M</sub>	330
Mass rod end	0.054 kg