



Xiangtan Huaxing Material Co., Ltd.



6024 Bearing 2D drawings and 3D CAD models

NTN SKF Auto Bearing 6024 Deep Groove Ball Bearings

Bearing No. 6024

Size	180x120x28 mm
Bore Diameter	180 mm
Outer Diameter	120 mm
Width	28 mm
d	120 mm
D	180 mm
B	28 mm
d ₁	139.05 mm
D ₂	165.3 mm
d _a - min.	129 mm
D _a - max.	171 mm
r _a - max.	2 mm
Basic dynamic load rating - C	88.4 kN
Basic static load rating - C ₀	80 kN
Fatigue load limit - P _u	2.8 kN
Reference speed	7500 r/min
Limiting speed	4800 r/min
Calculation factor - k _r	0.025
Calculation factor - f ₀	15.9
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.16



Xiangtan Huaxing Material Co., Ltd.

EAN	7316576621499
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	120MM Bore; 180MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6024
Weight / LBS	4.75
Outside Diameter	7.087 Inch 180 Millimeter
Bore	4.724 Inch 120 Millimeter
Outer Race Width	1.102 Inch 28 Millimeter
bore diameter:	120 mm
static load capacity:	80 kN
outside diameter:	180 mm
precision rating:	ABEC 1 (ISO Class Normal)



Xiangtan Huaxing Material Co., Ltd.

overall width:	28 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	4800 RPM
internal clearance:	C0
series:	60
dynamic load capacity:	88.4 kN
d_1	139.05 mm
D_2	165.3 mm
$r_{1,2}$ min.	2 mm
d_a min.	129 mm
D_a max.	171 mm
r_a max.	2 mm
Basic dynamic load rating C	88.4 kN
Basic static load rating C_0	80 kN
Fatigue load limit P_u	2.75 kN
Calculation factor k_r	0.025
Calculation factor f_0	15.9
Mass bearing	2.1 kg